

This listing of claims will replace all prior versions, and listings, of claims in the application:

The Status of the Claims

1. (Canceled).
2. (Previously presented) The door of claim 15, wherein the door member comprises a second door panel that is movable.
3. (Previously presented) The door of claim 15, wherein the door is associated with a wall having a doorway, and the door member is stationary and adjacent to the wall.
4. (Previously presented) The door of claim 15, wherein the door is associated with a wall and a floor that define a doorway, and the door member comprises an upwardly facing surface of the floor.
5. (Previously presented) The door of claim 4, wherein at least a portion of the air outlet is situated to discharge at least a portion of the air toward the floor, whereby the air discharged from the outlet may help keep the floor dry.
6. (Previously presented) The door of claim 15, wherein the air inlet, the air outlet, and the elongate passageway remain in fluid communication with the atmosphere when the door is closed.
7. (Previously presented) The door of claim 15, wherein the blower continues to force air through the air passageway when the door is open.

8. (Previously presented) The door of claim 15, wherein the blower moves with the door panel.
9. (Previously presented) The door of claim 15, further comprising a flexible hose that couples the blower to the inflatable seal.
10. (Previously presented) The door of claim 15, wherein the door panel translates relative to the door member.
11. (Previously presented) The door of claim 15, wherein the door panel includes an upper edge and a substantially vertical edge, and the inflatable seal includes an L-shaped section that is adjacent to the upper edge and the substantially vertical edge.
12. (Previously presented) The door of claim 15, wherein the door panel includes a lower edge and a substantially vertical edge, and the inflatable seal includes an L-shaped section that extends along the lower edge and the substantially vertical edge.
13. (Previously presented) The door of claim 15, wherein the air at the air inlet is warmer than the air at the air outlet.
14. (Previously presented) The door of claim 15, further comprising a heater in heat transfer relationship with the air being forced through the inflatable seal.

15. (Currently amended) A door exposed to an atmosphere of air, comprising:
- a door member;
 - a door panel that is movable relative to the door member;
 - an inflatable seal between the door member and the door panel, wherein the inflatable seal defines an air inlet, and an air outlet, and includes an inner surface and an outer surface, wherein the inner surface defines an elongate air passageway therebetween between the air inlet and the air outlet and the outer surface is adapted to be in contact with the door member and the door panel;
 - a blower connected in fluid communication with the inflatable seal such that the blower forces the air in series flow from the atmosphere, through the air inlet, through the elongate air passageway such that the air is in direct contact with the inner surface, through the air outlet, and back to the atmosphere; and
 - thermal insulation, at least a portion of which is disposed inside the elongate air passageway such that it is adjacent the inner surface.

16. (Original) The door of claim 15, wherein the elongate air passageway includes some areas that are more thermally insulated than other areas of the elongate air passageway.

17-33. (Canceled).

34. (Previously presented) The door of claim 40, wherein the fluid mover comprises a pump.

35. (Previously presented) The door of claim 40, wherein the fluid mover comprises a blower.

36. (Previously presented) The door of claim 40, further comprising a heater in heat transfer relationship with the fluid.

37. (Previously presented) The door of claim 40, wherein the door member comprises a second door panel that is movable.

38. (Previously presented) The door of claim 40, wherein the door is associated with a wall having a doorway, and the door member is stationary and adjacent to the wall.

39. (Previously presented) The door of claim 40, wherein the door is associated with a wall and a floor that define a doorway, and the door member comprises an upwardly facing surface of the floor.

40. (Currently amended) A door, comprising:

a door member;

a door panel that is movable relative to the door member;

a pliable seal between the door member and the door panel, wherein the pliable seal includes an inner surface that defines an elongate passageway and an outer surface adapted to be in contact with the door member and the door panel therebetween;

a fluid disposed inside the pliable seal such that it is in contact with the inner surface;

a fluid mover having an inlet and an outlet in fluid communication with the elongate passageway, wherein the fluid mover forces the fluid to circulate in series through the outlet, through the elongate passageway, through the inlet, and back through the fluid mover; and

thermal insulation, at least a portion of which is disposed inside the elongate passageway, adjacent the inner surface.

41. (Original) The door of claim 40, wherein the elongate passageway includes some areas that are more thermally insulated than other areas of the elongate passageway.

42. (Canceled).

43. (Previously presented) The door of claim 48, wherein at least a portion of the heater is disposed inside the elongate passageway.

44. (Previously presented) The door of claim 48, wherein the fluid is pressurized.

45. (Previously presented) The door of claim 48, wherein the door member comprises a second door panel that is movable.

46. (Previously presented) The door of claim 48, wherein the door is associated with a wall having a doorway, and the door member is stationary and adjacent to the wall.

47. (Previously presented) The door of claim 48, wherein the door is associated with a wall and a floor that define a doorway, and the door member comprises an upwardly facing surface of the floor.

48. (Currently amended) A door, comprising:

a door member;

a door panel that is movable relative to the door member;

a pliable seal between the door member and the door panel, ~~wherein~~ the pliable seal includes an inner surface that defines an elongate passageway and an outer surface adapted to be in contact with the door member and the door panel therebetween;

a fluid disposed inside the pliable seal such that it is in contact with the inner surface;

a heater in heat transfer relationship with the fluid; and

thermal insulation, at least a portion of which is disposed inside the elongate passageway, adjacent the inner surface.

49. (Original) The door of claim 48, wherein the elongate passageway includes some areas that are more thermally insulated than other areas of the elongate passageway.

50. (New) A door exposed to an atmosphere of air, comprising:

a door member;

a door panel that is movable relative to the door member;

a pliable seal between the door member and the door panel, wherein the pliable seal defines an air inlet and an air outlet and includes an inner surface that defines an elongate air passageway between the air inlet and the air outlet;

a blower connected in fluid communication with the pliable seal such that the blower forces the air in series flow from the atmosphere, through the air inlet, through the elongate air passageway, through the air outlet, and back to the atmosphere; and

thermal insulation overlaying a portion of the inner surface such that it does not entirely cover the inner surface.

51. (New) The door of claim 50 wherein the thermal insulation is more rigid than the pliable seal.